

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC

www.erskineattachments.com  
800.437.6912

## **MINI HYDRAULIC SNOWBLOWER**

**MINI SKID STEER ATTACHMENT**



**BLOWN' AWAY...**

A quality built snowblower that really works! The Mini Hydraulic Snowblower meets the tough demands of your mini skid steer throwing snow up to 25' while clearing paths down to the ground. Featuring a No-Freeze-Up chute design! Two important factors must be considered when purchasing a snowblower – gallons per minute and hydraulic pressure (psi) are very important to the ultimate performance and your satisfaction. Every snowblower is custom engineered to provide maximum performance for each mini skid steer make and model.

### **FEATURES**

- Replaceable bolt-on high-carbon steel cutting edge
- Hydraulic control valve with electric solenoid controls all chute functions
- No-Freeze-Up chute design seals out snow and freezing slush (comes standard).
- Heavy-Duty gear box drives auger.
- Hydraulic chute rotation allows choice of casting direction.
- High-Carbon steel cutting edge comes standard.

**800.437.6912**

© 2019 Erskine Attachments, LLC. All rights reserved.

022819

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC

**MINI HYDRAULIC SNOWBLOWER****MINI SKID STEER ATTACHMENT**

Model	1600	2020 48"	2020 55"	2020 61"
Part Number	900455	901443	901445	901447
Stage	2	2	2	2
Width of Cut	53"	48"	55"	61"
Cutting Height	22"	29"	29"	29"
Cutting Edge	3/8" x 3" bolt-on	5/8" x 6" bolt-on	5/8" x 6" bolt-on	5/8" x 6" bolt-on
Auger Diameter	12" open flight	16" open flight	16" open flight	16" open flight
Fan Diameter	16" 4-blade	20" 4-blade	20" 4-blade	20" 4-blade
Chute Rotation	Hydraulic 210°	Hydraulic 270°	Hydraulic 270°	Hydraulic 270°
Pressure Relief	Fan Only	Auger	Auger	Auger
Casting Distance	Up to 25'	Up to 40'	Up to 40'	Up to 40'
Approimate Shipping Weight	418 lb.	652 lb.	700 lb.	725 lb.
Mounting Plate	Mini Skid Steer	Mini Skid Steer	Mini Skid Steer	Mini Skid Steer
Hoses	Included	Included	Included	Included
Hydraulic Flow	10-14 GPM	11-16 GPM	11-16 GPM	11-16 GPM
Operating Pressure	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi	2,500-3,500 psi
Skid Shoes	Standard	Standard	Standard	Standard
Mounting Kit Configurations	ASV/Terex (RC/PT30)			
	Bobcat (MT-52/55, 463/S70)			
	Toro / Vermeer / Boxer / Ditch Witch / Ramrod / Kanga / Cormidi			
	Universal Mounting Plate (up to 1,000 lb. ROC and within rated flow)			

Options				
Serrated Auger	N/A			
Hardened Skid Shoes	N/A			
Urethane Skid Shoes	N/A			
Urethane Cutting Edge				
Rubber Cutting Edge	N/A			
Toggle Control Harness		N/A	N/A	N/A
Pistol Grip Control Harness	N/A			
Loader Specific Wire Harness				
Factory Installed Couplers				



**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC

www.erskineattachments.com

800.437.6912

## MINI HYDRAULIC SNOWBLOWER


### MINI SKID STEER ATTACHMENT

Hydraulic chute rotation is standard equipment. The design eliminates metal-to-metal contact between the blower and the rotating chute base, preventing freeze-up under any conditions.

**NO-FREEZE-UP CHUTE**  
design seals out snow and freezing slush (comes standard)

**HEAVY-DUTY** gear box drives auger

Optional:  
Urethane Protective  
Cutting Edges.



Optional:  
Wire Harness for hydraulic  
models with attachment  
controls.



● **4-BLADE FAN**

Standard high-carbon steel cutting edge  
Optional protective urethane cutting edge is available

**EATON** | Char-Lynn



Casts snow up to 25' away



Hydraulic chute rotation allows choice of casting direction

**800.437.6912**

© 2019 Erskine Attachments, LLC. All rights reserved.

022819

**ERSKINE**<sup>®</sup>  
ATTACHMENTS LLC